

## IP CAMERA RANGE - 3 MP



### AD-IPC2R8L

- 4 Array IR LED, 80 Mtrs IR Distance
- 5-50mm Vari Focal Lens (2.8-12mm Optional)
- POE Support (Optional)
- Audio in / out (Optional)
- TF Card (Optional)

- 1/2.8" Sony EXMOR IP Bullet Camera
- 3 Mega Pixel (1080p) Full HD Resolution
- DWDR (100DB), ICR, 3DNR, AWB, AGC, BLC
- POE, Cloud Enabled, Vandal Proof, IP66

**3**  
MEGA  
PIXEL

CAMERA

**H.264**

COMPRESSION

**IP66**

PROTECTION

**64**  
GB

SD CARD  
SUPPORT  
(OPTIONAL)

**IR**

LEDS

**DN**

DAY NIGHT

**PoE**

SUPPORT  
(OPTIONAL)

### SPECIFICATION

Image Sensor	1/ 2.8"3 Megapixel SONY EXMOR cmos
Effective Pixels	2096x1561 pixels
Lens	5-50MM vary focal lens LENS
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual,1/25~1/10000
Min. Illumination	0.3Lux/F1.2 (Color)
SNR Ratio	>50Db
Day and Night	True day and night, DEFOG
WDR	YES
White Balance	YES
A.G.C	YES
Digital Noise Reduction	2D/3DNR
Privacy Masking	4 Zone Privacy Masking, Motion detection, temper alarm
Compression	H.264/MPEG4/MJPEG
Frame rate	Main Stream 1920*1080 (1 ~ 25/30fps) Sub Stream D1/CIF (1 ~ 25/30fps)
Bit Rate	32 Kbps~16Mbps
Protocol	HTTP, TCP/IP, RTSP, FTP, SMTP, DHCP, DNS, DDNS, PPPOE, NTP, UPnP
I/O Ports	Mic in, Audio out, RS485, RJ45, BNC out, SD Card
Onvif	Onvif Ver 2.0 (s)
Network Interface	RJ-45 10M/100M Base-T Ethernet interface
Power	DC12V ±5% , POE+
Operation Temperature	-10°C to +60°C
Housing Color	White
Material	Metal, Vandal resistance, built in heater & fan
Weight	950GM