

# 2 MP PIN Hole Camera

## IP PIN HOLE CAMERA - 2MP

AD-IPC-PH2

- ★ 1/2.8" 2MP Progressive cmos sensor
- ★ 2.8mm Lens (3.6mm, 6mm Optional)
- ★ 2 MP -Full HD Resolution
- ★ Plug and play, P2P service
- ★ Mobile viewing, Iphone & android app



## WI FI CUBE IP CAMERA - 2 MP

AD-IPC-C20W

- ★ 1/3" 1080P Progressive cmos sensor
- ★ 2.8mm Wide Angle Lens (3.6mm, 6mm Optional)
- ★ 15 Mtrs. IR Distance
- ★ 2 Mega Pixel Resolution
- ★ POE (Optional), P2P service



### Specification

<b>Image sensor</b>	<b>1 / 2.8" 2 megapixel progressive cmos sensor</b>
Min. Illumination	color: 0.01 lux @(f1.2,agc on),0 lux with ir
Lens	2.8mm fixed lens
Electronic shutter	auto (1/25s-1/10000s adjustable)
Day/night	auto/colour/b&w (Ir cut)
S/n ratio	≥ 55 db
Noise reduction	2d/3d digital noise reduction
Anti fog	yes
Wdr	digital wdr
Image adjustment	sharpness, brightness, saturation, Contrast adjustable
Video encoding	h.264
Encoding type	h.264-high profile/mainprofile/base line
Record resolution	main stream : 1920*1080@25fps/30fps, 1280*960@25fps/30fps, cif@25fps/30fps
Video bit rate control	support vbr/cbr
Video bit range	32kbps-8152kbps
Audio	Optional
Zoom	digital
Network interface	rj 45 10m/100m adaptive ethernet interface
Motion detection	multiple detection zone, variable sensity levels
ROI	support
Privacy masking	four zones for privacy masking
Snapshot	jpeg capture, capture resolution is the max Coding resolution
Security features	support password protection, water marking features
Text overlay	support (channel name and time title )
Alarm	support network anomaly, mask alarm and etc.
<b>Intelligent function</b>	<b>support line crossing detection</b>
Mobile app	ios, android
Network function	ipv4 / ipv6, http, https, 802.1x, qos, ftp, smtp, upnp, Snmp, dns, ddns, ntp, rtsp, rtp, tcp, udp, l gmp, lcmp, dhcp, pppoe
Protocol	support onvif and cgi protocol
Protection grade	ip65
Poe	yes (optional)
Power	dc 12v
Operation temperature	-10°c-60°c(14°f-122°f)
Power supply	8w max

<b>Image sensor</b>	<b>1 / 3" 1080p progressive cmos sensor</b>
Min. Illumination	color: 0.01 lux @(f1.2,agc on),0 lux with ir
Lens	2.8mm fixed lens
Ir distance	15 mtrs
Electronic shutter	auto (1/25s-1/10000s adjustable)
Day/night	auto/colour/b&w (Ir cut)
S/n ratio	≥ 55 db
Noise reduction	2d/3d digital noise reduction
Anti fog	no
Wdr	digital wdr
Image adjustment	sharpness, brightness, saturation, contrast Adjustable
Video encoding	h.264
Encoding type	h.264-high profile/mainprofile/base line
Record resolution	main stream : 1920*1080@25fps/30fps, cif@25fps/30fps
Video bit rate control	support vbr/cbr
Video bit range	32kbps-8152kbps
Audio	inbuilt audio : 1 audio out
Alarm	1 alarm input
Storage	support tf card (max 64gb)
Zoom	digital
Reset button	built in reset button
Network Interface	rj 45 10m/100m adaptive ethernet interface
Motion detection	multiple detection zone, variable sensitive levels
ROI	support
Privacy masking	four zones for privacy masking
Snapshot	jpeg capture, capture resolution is the max coding Resolution
Security features	support password protection, water marking Features
Text overlay	support (channel name and time title )
Alarm	support network anomaly, mask alarm and etc.
<b>Intelligent function</b>	<b>support line crossing detection</b>
Mobile app	ios, android
Network function	ipv4 / ipv6, http, https, 802.1x, qos, ftp, smtp, upnp,Snmp, dns, ddns, ntp, rtsp, rtp, tcp, udp, l gmp, lcmp, Dhcp, pppoe
Protocol	support onvif and cgi protocol
Protection grade	plastic casing
Power	dc 5v
Operation temperature	-10°c-60°c(14°f-122°f)
Power supply	6w max
Dimensions	66.6 mm * 99.5 mm * 131.2 mm
Weight	.35kg