

AD-32162HD5P

2 SATA 32ch Analog HD DVR E Series



- Support 32ch 4M unreal-time encoding;
- Support AHD, TVI,CVI, CVBS, IP video input;
- Support VGA maximum 1080P output, HDMI up to 4K output
- BIG1U Case, 2 SATA(Up to 16TB);
- 1*10/100/1000Mbps auto-sensing Ethernet port, RJ45 port ;
- Automatic networking support, a key to add equipment;
- Support the Onvif protocol;
- Support GB28181 (Optional);
- Cloud services, P2P, alarm information push to phone;
- Support remote access, support ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc ;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Support for more than twenty languages;
- Perfect protection circuit, unique triple watchdog function
- Support WEB, CMS, VMS, MYEYE Platform;

Specifications		
System	processor	Hi3531A
	Codec	H.264
	preview	32*4M@15fps(AHD) 32*3M@18fps(AHD) 32*1080P (5 in 1)
	Encode	32*4M@8fps(AHD) 32*3M@10fps(AHD) 32*1080P @15fps (5 in 1) 32*720P(5 in 1)
Video	Decode	16*4M@8fps(AHD) 16*3M@10fps(AHD) 16*1080P @15fps (5 in 1) 16*720P(5 in 1)
	Multi-mode	Analog:32*4M@8fps(AHD) 32*3M@10fps(AHD) 32*1080P @15fps (5 in 1) 32*720P(5 in 1) IP: 32*1080P;16*3M ;8*5M
	Playback	16ch
Audio	Compression	G.711a
	Intercom	Support
Management	Record mode	Manual>Alarm>Motion detection>Timing
	Inquire mode	Inquire by Time/Calendar/Event/Channel
	Storage mode	HDD Storage, Network Storage
	Backup	Network, USB, SATA
Interface	Video input	32*BNCSupport Coaxitron
	HDMI output	1*HDMI (MAX:4K)
	VGA output	1*VGA (MAX:1080P)
	Audio I/O	16/1
	Alarm I/O	8/1
	Ethernet port	1*10/100Mbps Ethernet port, RJ45 port
	PTZ control	1*RS485, 1 Rs232 Support for multiple PTZ protocol
	USB Port	2*USB2.0 ports
	HDD	2*SATA interface (Up to 8TB)
General	Temperature	0 - + 55
	Humidity	10% -90% RH
	Power supply	12V/4A
	Consumption	<10WWithout HDD
	Weight	Around 3KG
	Dimension	440mm(L)*290mm(W)* 50mm(H)

