

AD-60082V



- 8 CH NVR (96MBPS INPUT BANDWIDTH)
- FACE DETECTION, INTRUSION ALARM INBUILT ANALYTICS NVR
- MAXIMUM RECORDING RESOLUTION OF NVR IS 6MP
- 2 SATA HDD (6TB MAX), CLOUD NVR
- DROP BOX, GOOGLE DRIVE SUPPORTED FOR CLOUD RECORDING
- ONVIF SUPPORT

Specification

OPERATION SYSTEM	Embedded LINUX
PENTAPLEX FUNCTION	Live monitoring, recording, playback, backup & remote access
CONTROL MODE	Front panel, USB mouse, IR remote control, Network
VIDEO IP CAMERA INPUT	8 ch (96mbps input)
VIDEO DECODING CAPABILITY	8 ch - 6mp @ 30 fps
SUPPORT PROTOCOL	ONVIF 2.4
VIDEO STANDARD	PAL (625line, 50f/s) NTSC (525line, 60f/s)
VIDEO OUTPUT	1 CVBS, BNC (1.0Vp-p,75 ohms), 1 HDMI, 2.0, support 3840 x 2160, 1920x1080 Resolution, 1 VGA,1920x1080,1440x900, 1280x1024,1024x768,800x600 Resolution
AUDIO OUTPUT	1 RCA (Line out, 2.0Vp-p,300 ohms)
INTELLIGENT FEATURES	FACE DETECTION , INTRUSION ALARM (OPTIONAL)
DISPLAY IP RESOLUTION	"Main stream:up to 4096x3072 Auxiliary stream:4CIF"
DISPLAY RESOLUTION	6MP/5MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
FRAME RATE	1~30fps
ALARM IN	8 CH ALARM IN
ALARM OUT	3 CH ALARM OUT
TOUR DISPLAY	Support
PRIVACY MASKING	Four zones for privacy masking for each channel
VIDEO COMPRESSION	MPEG-4/H.264(High Profile@Level4.2)
AUDIO COMPRESSION	G.711A
IMAGE ENCODING	Adjustable encoding quality, variable code stream/fixed code stream
DUAL STREAM	Support
RECORDING MODE	Manual, auto, motion detection, stop
TIME BAR	Support
TRIGGER EVENTS	Recording, PTZ, Tour, Email
MOTION DETECTION	396 (22x18) detection zone, variable sensitivity levels
CAPTURE	JPEG capture
MAX PLAYBACK	1 / 2 / 4 / 8
BACKUP MODE	USB,HDD,Network Backup
ETHERNET	1 RJ-45 port (10M/100M/1000M)
NETWORK PROTOCOL	TCP/IP, UDP, HTTP, RTP/RTSP
NETWORK FUNCTION	DHCP, PPPOE, DDNS,SMTP,SNTP,FTP,UPnP,P2P,3G
REMOTE OPERATION	Monitoring, PTZ control, playback, system setting, file download, log information
SMART PHONE	iPhone, iPad, Android
HARD DISK	2 SATA ports, each SATA supports 6TB
HDD MANAGEMENT	Hard disk hibernation technology, HDD faulty alarm & raid
USB INTERFACE	2 USB 2.0 ports
RS485	Standard 485, half duplex,PTZ control
POWER SUPPLY	110V~220V±10% 47Hz-63Hz



CLOUD



MOBILE
SUPPORT



CMS



HDMI



PRODUCT
OF INDIA
BEST
QUALITY