

HDCVI 2MP (DVR)

HIGH DEFINITION VIDEO RECORDS
FOR FULL DETAILED FOOTAGE



AD-4I1CVIT

- 4 CH 1080P Realtime DVR
- 4 Video + 1 Audio DVR
- 1 Sata Upto 4 TB, 2 USB, VGA, HDMI, Remote
- Cloud Facility, Tribrid DVR, Maximum 2 IP Camera Support

AD-8I1CVIT

- 8 CH 960P Realtime DVR
- 8 Video + 1 Audio DVR
- 1 Sata Upto 4 TB, 2 USB, VGA, HDMI, Remote
- Cloud Facility, Tribrid DVR, Maximum 4 IP Camera Support

AD-16I2CVIT

- 16 CH 960P Realtime DVR
- 16 Video + 1 Audio DVR
- 2 Sata Upto 4 TB, 2 USB, VGA, HDMI, Remote
- Cloud Facility, Tribrid DVR, Maximum 4 IP Camera Support

- Support HDCVI/Analog/IP Video input
- H.264 dual-stream video compression
- All channel 720P realtime, 1080P non-realtime recording
- HDMI/VGA simultaneous video output
- 4/8/16 channel synchronous realtime playback, GRID interface & smart search
- ONVIF Version 2.4 conformance
- 3D intelligent positioning with PTZ dome camera
- Support 1 SATA HDD up to 4TB, 2 USB2.0
- Multiple network monitoring: Web viewer, CMS(VMS) & Smart Phone(MMS)



CLOUD



MOBILE
SUPPORT



CMS



HDMI



3G
NETWORK



BEST
QUALITY

SPECIFICATION

Model	SCVR5104-S2	SCVR5108-S2	WCVR5216-S2	
System	Main processor H.264High Profile video compression			
Video	Input	4CH BNC	8CH BNC	16CH BNC
	Output	1 VGA, 1 HDMI		
	Standard	HDCVI: 1080P/720P HDCVI camera IP: 1080P/720P IP camera Analog: 960H Analog camera		
Audio	Input	1 Channel, RCA		
	Output	1 Channel, RCA		
	Compression	G.711A		
	Intercom	support		
Recording Playback	Record mode	Manual>alarm>motion detection>timing		
	Record Rate	Main Stream: 1080P(1~15fps)/ 720P/960H/D1 (1~25/30fps) Extra Stream: CIF/QCIF(1~25/30fps), D1(1~6/7fps)		
	Resolution	720P(1280x720), D1(P:704x576/N:704x480), CIF(352x288/ 352x240)		
	Sync Playback	1/4	1/4/9	1/4/9/16
Storage and backup	Space occupation	960H : 12~20G/ day*channel 720P : ~20G/ day*channel audio : 691.2M/ day*channel		
	Backup mode	Network backup, USB HDD, USB writer, SATA writer		
Network	Ethernet	RJ-45 port(10/100M)		
	Network	HTTP, Ipv4, Ipv6, TCP/IP, SMTP, DHCP, DNS, PPPOE, DDNS, NTP P2P		
	Web Browser	IE6-10, Google Chrome, Firefox		
	Smart Phone	iPhone, ipad, Android		
Interface	Alarm input	No		
	Alarm output	No		
	PTZ control	Rs485: support multiple PTZ protocols		
	USB	3 USB ports		
	Hard disk	1 SATA (Each maximum support 4T)	2 SATA	
	Wireless	3G WIFI(expand via USB)		
	Power	12V		
	Dimension	CVR : 258*236*42mm, Box Size:300*115*290mm, Carton Size:630*320*620mm (10pcs/CTN)		
	Weight	CVR: 1.45kg (Without HDD), Carton Weight:16KG (10pcs/CTN)		