

IP CAMERA - 1.3 MP



AD-IPCCI0W

- 1/4.4" CMOS IP Cube Camera
- 2.8mm Wide Angle Lens (3.6mm, 6mm Optional)
- 10 IR LED, 15 Mtrs IR Distance
- Cloud Enabled, WIFI, Built in Mic, Audio Out, with Power Adaptor
- DWDR (100DB), ICR, 3DNR, AWB, AGC, BLC
- 1/3" Sony EXMOR IP Bullet Camera
- 1.3 Mega Pixel Resolution
- POE (Optional), Cloud Enabled
- H.264, Support Dual Stream
- Onvif Compatible

1.3
MEGA
PIXEL

CAMERA

H.264

COMPRESSION

DN

DAY NIGHT

IR

LEDS

PoE

SUPPORT
(OPTIONAL)

SPECIFICATION

IMAGE SENSOR	1 / 4" 720P PROGRESSIVE CMOS Sensor
MIN. ILLUMINATION	Color: 0.01Lux @(F1.2,AGC ON),0 LUX with IR
LENS	2.8MM FIXED LENS
IR DISTANCE	15 MTRS
ELECTRONIC SHUTTER	AUTO (1/25S-1/100000S ADJUSTABLE)
DAY/NIGHT	AUTO/COLOUR/B&W (IR CUT)
S/N RATIO	≥ 55 DB
NOISE REDUCTION	2D/3D DIGITAL NOISE REDUCTION
ANTI FOG	NO
WDR	DIGITAL WDR
IMAGE ADJUSTMENT	SHARPNESS, BRIGHTNESS, SATURATION, CONTRAST ADJUSTABLE
VIDEO ENCODING	H.264
ENCODING TYPE	H.264-HIGH PROFILE/MAINPROFILE/BASE LINE
RECORD RESOLUTION	MAIN STREAM : 1280*720@25FPS/30FPS, CIF@25FPS/30FPS
VIDEO BIT RATE CONTROL	SUPPORT VBR/CBR
VIDEO BIT RANGE	32KBPS-8152KBPS
AUDIO	INBUILT AUDIO : 1 AUDIO OUT
ALARM	1 ALARM INPUT
STORAGE	SUPPORT TF CARD (MAX 64GB)
ZOOM	DIGITAL
RESET BUTTON	BUILT IN RESET BUTTON
NETWORK INTERFACE	RJ 45 10M/100M ADAPTIVE ETHERNET INTERFACE
MOTION DETECTION	MULTIPLE DETECTION ZONE, VARIABLE SENSITY LEVELS
ROI	SUPPORT
PRIVACY MASKING	FOUR ZONES FOR PRIVACY MASKING
SNAPSHOT	JPEG CAPTURE, CAPTURE REOLUTION IS THE MAX CODING RESOLUTION
SECURITY FEATURES	SUPPORT PASSWORD PROTECTION, WATERMARKING FEATURES
TEXT OVERLAY	SUPPORT (CHANNEL NAME AND TIME TITLE)
ALARM	SUPPORT NETWORK ANOMALY, MASK ALRAM AND ETC.
INTELLIGENT FUNCTION	SUPPORT LINE CROSSING DETECTION
MOBILE APP	IOS, ANDROID
NETWORK FUNCTION	IPv4 / IPv6, HTTP, HTTPS, 802.1x, Qos, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, ICMP, DHCP, PPPoE
PROTOCOL	SUPPORT ONVIF AND CGI PROTOCOL
PROTECTION GRADE	PLASTIC CASING
POWER	DC 5V
OPERATION TEMPERATURE	-10°C-60°C(14°F-122°F)
POWER SUPPLY	6W MAX
DIMENSIONS	66.6 MM * 99.5 MM * 131.2 MM
WEIGHT	.35KG