

AD-POE8

- SUPPORT 10/100MBPS FAST ETHERNET SWITCH
- PROVIDE UPTO 15.4 W FOR SINGLE PORT
- 4X AUTO MDIX POE PORT
- FULL WIRE SPEED NON BLOCKING TRANSMISSION
- STORE AND FORWARD SWITCHING METHOD
- STURDY RACK MOUNTABLE METAL CASE



Specification

PRODUCT NAME	9 PORT POE SWITCH WITH 8 POE PORT 15.4W
CONNECTOR	8* 10/100M COPPER CABLE RJ45PORTS (ALL PORTS SUPPORT MDI/MDIX)
TRANSFER MODE	STORE AND FORWARD
NETWORK MEDIUM	10 BASE T : CAT3,4,5 UTP, 100 BASE TX : CAT6 OR MORE UTP, TRANSMISSION DISTANCE 100 MTRS
BANDWIDTH	1.8GBPS (NON BLOCKING)
PERFORMANCE SPECIFICATION	NETWORK LETANCY (10 TO 100 MBPS) MAXIMUM DELAY LESS THAN 20 MICROSECONDS
PACKETS MEMORY	PACKETS BUFFER MEMORY : 128KB
DATABASE	ADDRESS BATABASE SIZE : 1000
NETWORK PROTOCOLS AND STANDARDS	IEEE 802.3i 10 BASET, IEEE 802.3U, 100 BASETX, IEEE 802.3X, IEEE 802.AF DTE POWER VIA MDI
LED STATUS	SYSTEM: POWER SUPPLY , EVERY PORT: CONNECTING , POE, WORKING STATUS
POWER	MAXIMUM POE POWER 120W, POWER INPUT : AC 24V
WORKING ENVIRONMENT	OPERATING TEMPERATURE : -20°C - 55°C , STORAGE TEMPERATURE -20°C - 75°C, OPERATING HUMIDITY : 10% - 95%, NON CONDENSING
RADIATION	CE MARK , COMMERCIAL , FCC PART 15 CLASSB, EN55022, CLASSB
SAFETY	CE MARK , ROHS
WARRANTY	1 YEAR WARRANTY (2 YEAR WARRANTY FOR POWER ADAPTER)