

AD-IPCD2R2A

- 1 / 2.8" 2 MEGAPIXEL PROGRESSIVE CMOS Sensor
- 3.6MM FIXED LENS, INBUILT AUDIO
- 24 IR LED SMART IR, 20 MTRS IR DISTANCE
- AGC, BLC, WDR(120DB), MASKING, MOTION DETECTION, ANTI FOG
- ONVIF



Specification

IMAGE SENSOR	1/2.8" PROGRESSIVE SCAN CMOS
MIN. ILLUMINATION	Colour:0.01 , IR ON:0LUX
LENS	3.6MM
IR DISTANCE	20 MTRS
ELECTRONIC SHUTTER	AUTO (1/25S-1/100000S ADJUSTABLE)
DAY/NIGHT	AUTO/COLOUR/B&W (IR CUT)
S/N RATIO	>_55DB
NOISE REDUCTION	2D/3D NOISE REDUCTION
ANTI FOG	YES
WDR	DWDR-100DB
IMAGE ADJUSTMENT	SHARPNESS, BRIGHNESS, SATURATION , CONTRAST ADJUSTABLE
VIDEO ENCODING	H.264
ENCODING TYPE	H.264 HIGH PROFILE / MAIN STREAM / SUB STREAM
RECORD RESOLUTION	MAIN STREAM : 1920*1080P@ 25/30FPS , 1280*720@25/30FPS
VIDEO BIT RATE CONTROL	SUPPORT VARIABLE/CONSTANT BIT RATE
VIDEO BIT RANGE	32KBPS-8152KBPS
AUDIO	YES (INBUILT)
ALARM	SUPPORT NETWORK ABNORMAL, MASK ALARM, MOTION ALARM
STORAGE	OPTIONAL
ZOOM	6X DIGITAL
NETWORK INTERFACE	RJ45 10/100 ADAPTIVE ETHERNET INTERFACE
MOTION DETECTION	Yes
ROI	SUPPORT
CORRIDOR MODE	OPTIONAL
PRIVACY MASKING	FOUR ZONES FOR PRIVACY MASKING
SNAPSHOT	JPEG CAPTURE
SECURITY FEATURES	SUPPORT PASSWORD PROTECTION , WATERMARKING
TEXT OVERLAY	SUPPORT (CHANNEL NAME AND TIME TITLE)
INTELLIGENT FUNCTION	SUPPORT LINE CROSSING DETECTION
MOBILE APP	SUPPORT
NETWORK FUNCTION	IPV4/IPV6, HTTPS, 802.1X , QOS, FTP, SMTP, UPNP, SNMP, DNS, DDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, ICMP, DHCP, PPPOE
PROTOCOL	SUPPORT ONVIF 2.4 , CGI PROTOCOL
PROTECTION GRADE	Ip66
POE	SUPPORT (OPTIONAL)
POWER	DC12V
OPERATION TEMPERATURE	-10°C - 60°C
POWER SUPPLY	8W MAX