

AD-I662HD5

2SATA 5 in one DVR DA Series

- Support 16ch 1080Pnon real-time encoding;
- Support AHD, TVI, CVI,CVBS, IP videoinput;
- HDMI/VGA simultaneous video output;
- 1U Case, 2 SATA(Up to 8TB);
- 1*10/100Mbps auto-sensing Ethernet port, RJ45 port;
- Automatic networking support, a key to add equipment;
- Support the Onvif protocol;
- Support GB28181 (Optional);
- Cloud services, P2P,alarm information push to phone;
- Support remote access, support ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Support for more than twenty languages;
- Perfect protection circuit, unique triple watchdog function;
- Support WEB, CMS, VMS, MYEYE Platform;



Specification

System	processor	Hi3531A
Video	Codec	H.264
	Encode	16*1080P@12fps; 8*1080P; 16*1080N
	Decode	16*1080P@12fps; 8*1080P; 16*1080N
	Multi-mode	Analog: 16*1080P@12fps; 8*1080P; 16*1080N Hybird:8*1080P(analog)+8*1080P(ip) IP:4*5M; 8*3M; 8*1080P+8*960P
Audio	Playback	16ch
	Compression	G.711a
Management	Intercom	Support
	Record mode	Manual>Alarm>Motion detection>Timing
Interface	Inquire mode	Inquire by Time/Calendar/Event/Channel
	Storage mode	HDD Storage, Network Storage
	Backup	Network, USB, SATA
	Video input	16*BNC(Support Coaxitron)
General	HDMI output	1*HDMI (MAX:4K)
	VGA output	1*VGA (MAX:1080P)
	Audio I/O	6/1
	Alarm I/O	4/1
	Ethernet port	1*10/100Mbps Ethernet port, RJ45 port
	PTZ control	1*RS485, Support for multiple PTZ protocol
	USB Port	3*USB2.0 ports
	HDD	2*SATA interface (Up to 8TB)
	Temperature	0°C - + 55°C
	Humidity	10% -90% RH
Power supply	12V/4A	
Consumption	<10W(Without HDD)	
Weight	Around 1.8KG	
Dimension	350mm(L)* 296mm(W)* 44mm(H)	