

AD-B2HDR6

- HIGH SPEED, LONG DISTANCE REALTIME TRANSMISSION
- AWB , AGC, BLC , DWDR, OSD
- 2.8-12MM VARI FOGAL LENS
- MAX. IR LED 42 , IR DISTANCE 60 MTRS
- IP68 OUTDOOR



Specification

SUB CATEGORY	AURA HD CAMERA
PRODUCT MODEL	AD-B2HDR6
IMAGE SENSOR	1/2.8" 2 MP AURA HD CMOS
MIN. ILLUMINATION	Color: 0.01Lux @(F1.2,AGC ON),0 LUX with IR
LENS	2.8-12MM VARI FOGAL LENS
IR DISTANCE	60 MTRS
ELECTRONIC SHUTTER	AUTO (1/25S-1/100000S ADJUSTABLE)
DAY/NIGHT	AUTO/COLOUR/B&W (IR CUT)
S/N RATIO	> 55 DB
NOISE REDUCTION	2D/3D DIGITAL NOISE REDUCTION (AUTO)
ANTI FOG	NO
WDR	DWDR
IMAGE ADJUSTMENT	OSD
RECORD RESOLUTION	1920*1080@25FPS/30FPS
CVBS OUTPUT	1 CH BNC AURA HD OUTPUT
PROTECTION GRADE	IP66, OUTDOOR
POE	NOT SUPPORTED
POWER	DC12V-2AMP
OPERATION TEMPERATURE	-20°-60° (14°-122°)
POWER SUPPLY	6W
WEIGHT	.80KG
TRANSMISSION DISTANCE	500 MTRS VIA COAXIAL CABLE

4 In 1

2 MP

OSD

DWDR

IR
CAMERA

Ip66

LOW
LUX

IP CAMERA

ONVIF