

IP BULLET CAMERA - 2MP



AD-IPCB2VFR6A

2
MEGA
PIXEL

CAMERA

H.264

COMPRESSION

DN

DAY NIGHT

IR

LEDS

Ip67

PROTECTION

PoE

SUPPORT
(OPTIONAL)

4X

OPTICAL
ZOOM

KEY FEATURES

- 2MP IP Bullet Varifocal Camera
- 42 IR LEDs, 60Mtrs.IR Distance
- 1/2.7" 2MP Progressive CMOS
- 2.8-12mm VariFoca Lens
- H.264, H.265 2MP Realtime Recording
- True Day/Night, 3D DNR, WDR
- PoE, IP67
- Audio In & Out Jack
- Corridor mode, Line Crossing Analytics
- Support P2P on Android & IOS Remote Monitoring

Specification

IMAGE SENSOR	1/2.7" 2 MEGAPIXEL PROGRESSIVE CMOS Sensor
MIN. ILLUMINATION	Color: 0.01Lux @(F1.2,AGC ON),0 LUX with IR
LENS	2.8 - 12mm VARI FOCAL
IR DISTANCE	60 MTRS IR RANGE
ELECTRONIC SHUTTER	AUTO (1/25S-1/100000S ADJUSTABLE)
DAY/NIGHT	AUTO/COLOUR/B&W (IR CUT)
S/N RATIO	≥ 55 DB
NOISE REDUCTION	2D/3D DIGITAL NOISE REDUCTION
ANTI FOG	YES
WDR	WDR 120DB
IMAGE ADJUSTMENT	SHARPNESS, BRIGHTNESS, SATURATION , CONTRAST ADJUSTABLE
VIDEO ENCODING	H.265, H.264
ENCODING TYPE	H.265: MAIN PROFILE , H.264 : HIGH PROFILE/MAIN PROFILE/BASE LINE PROFILE
RECORD RESOLUTION	MAIN STREAM : 2240*1680@20/25FPS, 2048*1536@25FPS/30FPS, 1920*1080@25FPS/ 30FPS, CIF@25FPS/30FPS
VIDEO BIT RATE CONTROL	SUPPORT VBR/CBR
VIDEO BIT RANGE	32KBPS-8152KBPS
AUDIO IN / OUT	YES
ALARM	OPTIONAL
STORAGE	NA
ZOOM	4X OPTICAL ZOOM, DIGITAL ZOOM
Rs485	NO
NETWORK INTERFACE	RJ 45 10M/100M ADAPTIVE ETHERNET INTERFACE
MOTION DETECTION	MULTIPLE DETECTION ZONE, VARIABLE SENSITY LEVELS
ROI	SUPPORT
CORRIDOR MODE	YES
PRIVACY MASKING	FOUR ZONES FOR PRIVACY MASKING
SNAPSHOT	JPEG CAPTURE, CAPTURE RESOLUTION IS THE MAX CODING RESOLUTION
SECURITY FEATURES	SUPPORT PASSWORD PROTECTION, WATERMARKING FEATURES
TEXT OVERLAY	SUPPORT (CHANNEL NAME AND TIME TITLE)
ALARM	SUPPORT NETWORK ANOMALY, MASK ALARM AND ETC.
INTELLIGENT FUNCTION	SUPPORT LINE CROSSING DETECTION
MOBILE APP	IOS, ANDROID
NETWORK FUNCTION	IPv4 / IPv6, HTTP, HTTPS, 802.1x, Qos, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, ICMP, DHCP, PPPoE
PROTOCOL	SUPPORT ONVIF AND CGI PROTOCOL
PROTECTION GRADE	IP67
POE	YES
POWER	DC 12V
OPERATION TEMPERATURE	-10°C-60°C(14°F-122°F)
POWER SUPPLY	8W MAX