

# Network Video Recorder (NVR)

## 64 CH NETWORK VIDEO RECORDER (NVR) INTELLIGENT, DIGITAL, HIGH DEFINITION

AD-70648V

- ★ 64 Channel NVR 256 Mbps input bandwidth
- ★ 8 Sata HDD (unlimited capacity)
- ★ 2 LAN port
- ★ Max Record Resolution 1080P
- ★ Unlimited TB each SATA Port
- ★ 2 way audio support



### Specification

Operation System		Embedded Linux
"Video Audio Input"	Voice Talk	1ch, RCA Interface(Line in,2Vpp,1 Kohms)
	Input Bandwidth	256Mbps
	IPC Input	64ch
Video Audio Output	VGA	1ch,1920×1080,1280×1024,1280×720,1024×768 Selectable
	HDMI	Ver. 2.0 3840×2160;1920×1080,1280×1024,1280×720,1024×768 Selectable
	Audio Output	1ch,RCA Interface(Line out,2Vpp,300ohms)
Encode	Audio Encode	G.711A
	Audio Bit Rate	64Kbps
Decode	"IP Channel Resolution"	"Main Stream: Up to 3264x2448Sub Stream: D1 MAX"
	"Video Decode Standard"	"H.265+, H.265(Main Profile@L5.0 High-tie)H.264(High Profile@Level5.0)"
	"Audio Decode Standard"	G.711A, G.726
	"Multi-channelPlayback"	32ch
	The Highest Decode Performance	16ch 1080P@30FPS
Other	Intelligent Function	N/A
	Voice Talk	Two-way Voice Talk
	Motion Detection	Each Channel Support 396 (22×18) Detection Area; Support Multi-level Sensitivity
HDD	Snapshot	Support jpeg Snapshot
	SATA Port	8
	ESATA Port	1
"External Interface"	Maximum Capacity	No Limitation
	Network Port	2 RJ45;10M/100M/1000M Suitable Ethernet Port
	USB Port	3 USB 2.0
	Alarm Input	16ch Switch
	Alarm Output	4ch Relay NO-NC
	RS-232	Support
	RS-485	Support, Half Duplex
Structure	PackIng	520x520x215mm
	Size	2U, 441x448x88mm
	Weight	7Kg (Not Include HDD)
Electrical	Installation	Rack Installation, Desktop Installation
	Power Supply	110V~220V±10% 47Hz~63Hz
	Operation Temperature	0℃~+55℃
	Operation humidity	10%~90%
Performance	Power	20W (Not Include HDD)