2 MP IP Camera

IR MINI PTZ CAMERA - 2MP

AD-IPC-SD102IR

★ 4.5" Metal & plastic body construction
★ 1/3" CMOS, 2.0 Megapixels, 10X optical zoom(5.1-51mm lens)
★ PWM function, intelligent IR illumination & power consumption is variable, dependant the zoom factor
★ IR distance 80M
★IP66 rate protection

Specification

Sensor	**1/3" 2.0M Pixel CMOS**
Effective pixels	1080P(1920X1080)
Total pixels	2.0 Megapixels
Output Pixel	1920*1080@30fps1920*1080@25fps
Lens	10X optical zoom f=5.1mm(W) ~ 51mm(T) ±5%
Iris	F1.6~F1.8
Min. illumination	Color: 0.1Lux\ B/W: 0.01Lux / IR ON:0 Lux
D/N	IR-CUT
BLC	Auto
WB	Auto/manual/indoor/outdoor
S/N Ratio	≥50dB
Dome	
Communications	TCP/IP, HTTP, FTP, RTSP, UPnP, DNS, NTP,
Protocol	RTP, UDP, IGMP
Software Control	IE, UC, Management Platform
Mobile View (optional)	Support Windows, Symbian, IPhone platform smartphone
Horizontal Rotation Speed	0.02°/s-45°/s
Horizontal Rotation Range	360°
Tilt Rotation Speed	0.02°/s-30°/s
Auto Flip	Horizontal 180°, Vertical 93°
A-B Scan	User programmable
A-B Scan Speed	1-9 levels setting available
Dwell Preset	1-60s interval available
Preset Points	250
Go to Preset Speed	01-64 levels available
PWR On Action	Memory/Tour 1/360° scan/A-B scan/Preset 1-8/None

Park Time	01-60mins available
Preset Points	220
Guard Tours	3 groups
Guard Points	Max.16 points, dwell time user selectable
Operating temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operation menu	English
Pan and Tilt position display	Support
Auto Control IR LED	PWM
LEDs Array	42Mil
IR distance	80 meters
Support ambient light detection	IR illumination on 1-15 grades selectable;
Humidity	≤95% Non Condensing
Power	DC12V 3A
Consumption	≤15W
Lightning Protection	Transient voltage 6000V

ONVIF FC CE RoHS